

## SCREW-LOCK BALL EXTENDED COOLANT NOZZLE FOR CNC LATHES


- Extended ball socket provides greater range of aimability than the **BlackEye** (page 25) while still being relatively compact
  - Ideal for tool positions where tool tip is difficult to reach with standard screw-lock ball (i.e. short tool projections)
    - Rated to 150 PSI maximum Sizes available to fit almost every machine or toolholder
      - Choose the orifice diameter to suit your application


## **DIMENSIONS IN INCHES** (except as noted)

Part No.	Nominal Dia. "D"	Orifice Dia. "d"	L	Pkg Qty
BUG02305	12 mm	.11	1.10	5
BUG02310	12 mm	.16	1.10	5
BUG02312	12 mm	M6 x 1.0	1.10	5
BUG02315	14 mm	.11	1.20	5
BUG02320	14 mm	.16	1.20	5
BUG02322	14 mm	M6 x 1.0	1.20	5
BUG02325	15 mm	.11	1.23	5
BUG02330	15 mm	.16	1.23	5
BUG02332	15 mm	M6 x 1.0	1.23	5
BUG02335	22 mm	.11	1.50	5
BUG02340	22 mm	.16	1.50	5
BUG02342	22 mm	M6 x 1.0	1.50	5
BUG02345	1/2 inch	.11	1.12	5
BUG02350	1/2 inch	.16	1.12	5
BUG02352	1/2 inch	M6 x 1.0	1.12	5
BUG02355	5/8 inch	.11	1.23	5
BUG02360	5/8 inch	.16	1.23	5
BUG02362	5/8 inch	M6 x 1.0	1.23	5

Material:
Body: Acetal
Ball: Stainless Steel
Maximum Pressure:
150 PSI (10 bar)

**Maximum Operating Temperature:** 160° F (70° C)





BugEye shown installed on CNC turning center.

**Ordering Information:** Measure the diameter of the original ball in your machine and order the nominal diameter to suit.